



## LED-Strips COB 8,2W/m



The LED Strip COB Short Cut offers perfect, uniform, and comfortable light without visible points or spots, creating an atmosphere that is both inviting and functional. Short distances between each cutting point, with only 13.9 mm per cutting length, provide flexible installation, allowing you to customize the lighting according to your needs and preferences. With 3-step MacAdam color consistency, you can be confident that our light remains stable and uniform over time. Choose between 2700K, 3000K, or 4000K color temperatures. This LED strip has a beam angle of 120° and a CRI of 90, accurately rendering colors in a natural way. Choose between variants with IP20 or IP65 ratings for both indoor and outdoor use.



SPECIFICATIONS  CCT (Color Temperature): 4000K  CRI / Ra: 90  Color Code: 940  Lumen Output [lm/ m]: 770lm/m  Efficiacy [lm/ W]: 93lm/w  MacAdam (SDCM): 3  Beam Angle: 120°  LED pr. meter: 504  System Voltage [V]: 24VDC  System Power [W/m]: 8,2  Dimming: Depending on Driver  Heat sink needed: No  Connection: Cable 2m  Cuttable [mm]: 13.89mm  Max. length [m]: 5m  Ingress Protection: IP20  Lifetime [h]: L80B10: 50.000h  Length: 5000mm  Width: 8mm  Weight: 0,065kg  Max width Led Strip: 8mm		
CRI / Ra:       90         Color Code:       940         Lumen Output [lm/ m]:       770lm/m         Efficiacy [lm/ W]:       93lm/w         MacAdam (SDCM):       3         Beam Angle:       120°         LED pr. meter:       504         System Voltage [V]:       24VDC         System Power [W/m]:       8,2         Dimming:       Depending on Driver         Heat sink needed:       No         Connection:       Cable 2m         Cuttable [mm]:       13.89mm         Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg		
Color Code:       940         Lumen Output [lm/ m]:       770lm/m         Efficiacy [lm/ W]:       93lm/w         MacAdam (SDCM):       3         Beam Angle:       120°         LED pr. meter:       504         System Voltage [V]:       24VDC         System Power [W/m]:       8,2         Dimming:       Depending on Driver         Heat sink needed:       No         Connection:       Cable 2m         Cuttable [mm]:       13.89mm         Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	•	4000K
Lumen Output [lm/ m]:       770lm/m         Efficiacy [lm/ W]:       93lm/w         MacAdam (SDCM):       3         Beam Angle:       120°         LED pr. meter:       504         System Voltage [V]:       24VDC         System Power [W/m]:       8,2         Dimming:       Depending on Driver         Heat sink needed:       No         Connection:       Cable 2m         Cuttable [mm]:       13.89mm         Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	CRI / Ra:	90
Efficiacy [lm/ W]:       93lm/w         MacAdam (SDCM):       3         Beam Angle:       120°         LED pr. meter:       504         System Voltage [V]:       24VDC         System Power [W/m]:       8,2         Dimming:       Depending on Driver         Heat sink needed:       No         Connection:       Cable 2m         Cuttable [mm]:       13.89mm         Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	Color Code:	940
MacAdam (SDCM):       3         Beam Angle:       120°         LED pr. meter:       504         System Voltage [V]:       24VDC         System Power [W/m]:       8,2         Dimming:       Depending on Driver         Heat sink needed:       No         Connection:       Cable 2m         Cuttable [mm]:       13.89mm         Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	Lumen Output [lm/ m]:	770lm/m
Beam Angle:       120°         LED pr. meter:       504         System Voltage [V]:       24VDC         System Power [W/m]:       8,2         Dimming:       Depending on Driver         Heat sink needed:       No         Connection:       Cable 2m         Cuttable [mm]:       13.89mm         Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	Efficiacy [lm/W]:	93lm/w
LED pr. meter:       504         System Voltage [V]:       24VDC         System Power [W/m]:       8,2         Dimming:       Depending on Driver         Heat sink needed:       No         Connection:       Cable 2m         Cuttable [mm]:       13.89mm         Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	MacAdam (SDCM):	3
System Voltage [V]:       24VDC         System Power [W/m]:       8,2         Dimming:       Depending on Driver         Heat sink needed:       No         Connection:       Cable 2m         Cuttable [mm]:       13.89mm         Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	Beam Angle:	120°
System Power [W/m]:       8,2         Dimming:       Depending on Driver         Heat sink needed:       No         Connection:       Cable 2m         Cuttable [mm]:       13.89mm         Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	LED pr. meter:	504
Dimming: Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 13.89mm  Max. length [m]: Ingress Protection: IP20 Lifetime [h]: Length: S000mm Width: Bmm Weight: O,065kg	System Voltage [V]:	24VDC
Heat sink needed:       No         Connection:       Cable 2m         Cuttable [mm]:       13.89mm         Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	System Power [W/m]:	8,2
Connection: Cable 2m  Cuttable [mm]: 13.89mm  Max. length [m]: 5m  Ingress Protection: IP20  Lifetime [h]: L80B10: 50.000h  Length: 5000mm  Width: 8mm  Weight: 0,065kg	Dimming:	Depending on Driver
Cuttable [mm]:       13.89mm         Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	Heat sink needed:	No
Max. length [m]:       5m         Ingress Protection:       IP20         Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	Connection:	Cable 2m
Ingress Protection:         IP20           Lifetime [h]:         L80B10: 50.000h           Length:         5000mm           Width:         8mm           Weight:         0,065kg	Cuttable [mm]:	13.89mm
Lifetime [h]:       L80B10: 50.000h         Length:       5000mm         Width:       8mm         Weight:       0,065kg	Max. length [m]:	5m
Length: 5000mm Width: 8mm Weight: 0,065kg	Ingress Protection:	IP20
Width: 8mm Weight: 0,065kg	Lifetime [h]:	L80B10: 50.000h
Weight: 0,065kg	Length:	5000mm
	Width:	8mm
Max width Led Strip: 8mm	Weight:	0,065kg
	Max width Led Strip:	8mm