



LED-Strips COB 17,6W/m



The LED Strip COB provides a perfectly uniform and pleasant light without visible points or spots, creating an atmosphere that is both inviting and functional. The LED strip has a high lumen value, allowing for flexible installation so you can customize the lighting according to your needs and preferences. With 3-step MacAdam color consistency, you can be confident that our light remains stable and uniform over time. Choose between 2700K, 3000K, or 4000K. This LED strip has a beam angle of 120° and CRI 90, rendering colors in a natural and accurate way.



SPECIFICATIONS 2700K CCT (Color Temperature): 2700K CRI / Ra: 90 Color Code: 927 Lumen Output [lm/ m]: 1380lm/m Efficiacy [lm/ W]: 86lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm		
CRI / Ra: 90 Color Code: 927 Lumen Output [lm/ m]: 1380lm/m Efficiacy [lm / W]: 86lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	SPECIFICATIONS	
Color Code: 927 Lumen Output [lm/ m]: 1380lm/m Efficiacy [lm/ W]: 86lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	CCT (Color Temperature):	2700K
Lumen Output [lm/ m]: 1380lm/m Efficiacy [lm/ W]: 86lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	CRI / Ra:	90
Efficiacy [lm/ W]: 86lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	Color Code:	927
MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	Lumen Output [lm/ m]:	1380lm/m
Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	Efficiacy [lm/W]:	86lm/w
LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	MacAdam (SDCM):	3
System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	Beam Angle:	120°
System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	LED pr. meter:	480
Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: Ingress Protection: Lifetime [h]: Length: 5020mm	System Voltage [V]:	24VDC
Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	System Power [W/m]:	16
Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	Dimming:	Depending on Driver
Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	Heat sink needed:	No
Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	Connection:	Cable 2m
Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm	Cuttable [mm]:	50mm
Lifetime [h]: L80B10: 50.000h Length: 5020mm	Max. length [m]:	5m
Length: 5020mm	Ingress Protection:	IP65
-	Lifetime [h]:	L80B10: 50.000h
Width: 10mm	Length:	5020mm
	Width:	10mm
Weight: 0,176kg	Weight:	0,176kg
Max width Led Strip : 10mm	Max width Led Strip :	10mm