



LED-Strips COB 17,6W/m



The LED Strip COB provides a perfectly uniform and pleasant light without visible points or spots, creating an atmosphere that is both inviting and functional. The LED strip has a high lumen value, allowing for flexible installation so you can customize the lighting according to your needs and preferences. With 3-step MacAdam color consistency, you can be confident that our light remains stable and uniform over time. Choose between 2700K, 3000K, or 4000K. This LED strip has a beam angle of 120° and CRI 90, rendering colors in a natural and accurate way.



SPECIFICATIONS CCT (Color Temperature): 4000K CRI / Ra: 90 Color Code: 940 Lumen Output [lm/ m]: 1600lm/m Efficiacy [lm/ W]: 100lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm		
CRI / Ra: 90 Color Code: 940 Lumen Output [lm/ m]: 1600lm/m Efficiacy [lm / W]: 100lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	SPECIFICATIONS	
Color Code: 940 Lumen Output [lm/ m]: 1600lm/m Efficiacy [lm/ W]: 100lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	CCT (Color Temperature):	4000K
Lumen Output [lm/ m]: 1600lm/m Efficiacy [lm/ W]: 100lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	CRI / Ra:	90
Efficiacy [lm / W]: 100lm/w MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	Color Code:	940
MacAdam (SDCM): 3 Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	Lumen Output [lm/ m]:	1600lm/m
Beam Angle: 120° LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	Efficiacy [lm/W]:	100lm/w
LED pr. meter: 480 System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	MacAdam (SDCM):	3
System Voltage [V]: 24VDC System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	Beam Angle:	120°
System Power [W/m]: 16 Dimming: Depending on Driver Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	LED pr. meter:	480
Dimming: Heat sink needed: No Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: Ingress Protection: Lifetime [h]: Length: 5020mm Width:	System Voltage [V]:	24VDC
Heat sink needed: Connection: Cable 2m Cuttable [mm]: Max. length [m]: Ingress Protection: Lifetime [h]: Length: Width: No Cable 2m Somm IP65 LENDER SOMM LENDER SOMM LENDER SOMM No LENDER SOMM LENDER SOMM No NO LENDER SOMM NO LENDER SOMM	System Power [W/m]:	16
Connection: Cable 2m Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	Dimming:	Depending on Driver
Cuttable [mm]: 50mm Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	Heat sink needed:	No
Max. length [m]: 5m Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	Connection:	Cable 2m
Ingress Protection: IP65 Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	Cuttable [mm]:	50mm
Lifetime [h]: L80B10: 50.000h Length: 5020mm Width: 10mm	Max. length [m]:	5m
Length: 5020mm Width: 10mm	Ingress Protection:	IP65
Width: 10mm	Lifetime [h]:	L80B10: 50.000h
	Length:	5020mm
Weight: 0.176kg	Width:	10mm
vveignt. 0,1/okg	Weight:	0,176kg
Max width Led Strip : 10mm	Max width Led Strip:	10mm