



**PRODUCT FAMILY SHEET**  
Trimo Micro



# Trimo Micro

Tired of downlights giving obtrusive light? This particular model requires a hole dimension of only 90mm. This makes it very versatile with a minimum of stray light, this is accomplished by using a recessed LED light source. The Trimo Micro has a 18i3 connector and can be supplied with a variety of connector solutions.

## VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
18015-7-40-2	13	2150	1240	3000	40°	Clear	80	Black	None	18i3 Quick connectio
18015-7-30-3- ddd	13	2150	1205	3000	30°	Clear	80	White	DALI	5 DALI Quick connect
18015-7-30-2	13	2150	1205	3000	30°	Clear	80	Black	None	18i3 Quick connectio
18015-7-30-2- ddd	13	2150	1205	3000	30°	Clear	80	Black	DALI	5 DALI Quick connect
18015-7-50-3	13	2150	1318	3000	50°	Clear	80	White	None	18i3 Quick connectio
18015-7-40-3	13	2150	1240	3000	40°	Clear	80	White	None	18i3 Quick connectio