




Trimo Mini








| C € □ □ □ 230V 50Hz | A** - A |
|----------------------------|----------------|
| SPECIFICATIONS | |
| Lightsource Type: | LED (built in) |
| System Power [W]: | 24W |
| CCT (Color Tomporatura). | 20001/ |

| SPECIFICATIONS | |
|-------------------------------|-----------------------|
| Lightsource Type: | LED (built in) |
| System Power [W]: | 24W |
| CCT (Color Temperature): | 3000K |
| CRI / Ra: | 80 |
| Lumen Output: | 2940lm |
| Lumen LED (tc=25): | 3650lm |
| Beam Angle: | 24° |
| Lens (Diffuser): | Clear |
| Dimming: | None |
| System Voltage [V]: | 230V 50Hz |
| Connection: | 18i3 Quick connection |
| Mounting: | Recessed, Ceiling |
| Cut-out [mm]: | Ø112mm |
| Lifetime [h]: | L80B10: 100 000h |
| Lumen/W: | 123lm/W |
| MacAdam (SDCM): | 3 |
| Color: | Black |
| Height [mm]: | 110mm |
| Width [mm]: | 122mm |
| Weight [kg]: | 0,7kg |
| To be recessed in insulation: | No |



Our Trimo range of downlights guarantees a minimum of stray light. This is accomplished by using a recessed LED light source. This model requires a hole dimension of 112mm in diameter making it very versatile providing very powerful light. The Trimo Mini has a 18i3 connector and is supplied with a variety of connector solutions.