




Trimo Mini







(€ ☐ [P20] 230V 50Hz





Lightsource Type: System Power [W]: CCT (Color Temperature): CRI / Ra: Lumen Output: Lumen LED (tc=25): Beam Angle: Lens (Diffuser): Dimming: None System Voltage [V]: Connection: Mounting: Cut-out [mm]: Lifetime [h]: Lumen/W: MacAdam (SDCM): Color: White Height [mm]: Weight [kg]: To be recessed in insulation: MOUNK 24W 24W 24W 24W 24W 24W 24W 24	SPECIFICATIONS	
System Power [W]: 24W CCT (Color Temperature): 3000K CRI / Ra: 80 Lumen Output: 2890lm Lumen LED (tc=25): 3650lm Beam Angle: 40° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: 18i3 Quick connection Mounting: Recessed, Ceiling Cut-out [mm]: Ø112mm Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg		LED (built in)
CRI / Ra: 80 Lumen Output: 2890lm Lumen LED (tc=25): 3650lm Beam Angle: 40° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: 18i3 Quick connection Mounting: Recessed, Ceiling Cut-out [mm]: Ø112mm Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg		24W
Lumen Output: 2890lm Lumen LED (tc=25): 3650lm Beam Angle: 40° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: 18i3 Quick connection Mounting: Recessed, Ceiling Cut-out [mm]: Ø112mm Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	CCT (Color Temperature):	3000К
Lumen LED (tc=25): 3650lm Beam Angle: 40° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: 18i3 Quick connection Mounting: Recessed, Ceiling Cut-out [mm]: Ø112mm Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	CRI / Ra:	80
Beam Angle: 40° Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: 18i3 Quick connection Mounting: Recessed, Ceiling Cut-out [mm]: Ø112mm Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	Lumen Output:	2890lm
Lens (Diffuser): Clear Dimming: None System Voltage [V]: 230V 50Hz Connection: 18i3 Quick connection Mounting: Recessed, Ceiling Cut-out [mm]: Ø112mm Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	Lumen LED (tc=25):	3650lm
Dimming: None System Voltage [V]: 230V 50Hz Connection: 18i3 Quick connection Mounting: Recessed, Ceiling Cut-out [mm]: Ø112mm Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	Beam Angle:	40°
System Voltage [V]: 230V 50Hz Connection: 18i3 Quick connection Mounting: Recessed, Ceiling Cut-out [mm]: Ø112mm Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	Lens (Diffuser):	Clear
Connection: 18i3 Quick connection Mounting: Recessed, Ceiling Cut-out [mm]: Ø112mm Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	Dimming:	None
Mounting: Recessed, Ceiling Cut-out [mm]: Ø112mm Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	System Voltage [V]:	230V 50Hz
Cut-out [mm]: Ø112mm Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	Connection:	18i3 Quick connection
Lifetime [h]: L80B10: 100 000h Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	Mounting:	Recessed, Ceiling
Lumen/W: 121lm/W MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	Cut-out [mm]:	Ø112mm
MacAdam (SDCM): 3 Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	Lifetime [h]:	L80B10: 100 000h
Color: White Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	Lumen/W:	121lm/W
Height [mm]: 110mm Width [mm]: 122mm Weight [kg]: 0,7kg	MacAdam (SDCM):	3
Width [mm]: 122mm Weight [kg]: 0,7kg	Color:	White
Weight [kg]: 0,7kg	Height [mm]:	110mm
3 - 3	Width [mm]:	122mm
To be recessed in insulation: No	Weight [kg]:	0,7kg
	To be recessed in insulation:	No

Our Trimo range of downlights guarantees a minimum of stray light. This is accomplished by using a recessed LED light source. This model requires a hole dimension of 112mm in diameter making it very versatile providing very powerful light. The Trimo Mini has a 18i3 connector and is supplied with a variety of connector solutions.