



PRODUCT SHEET

Stream Y

Art. no: 102452-E-02



Lighting Solutions

Stream Y



SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	42W
CCT (Color Temperature):	4000K
CRI / Ra:	80
Lumen Output:	6600lm
Lumen LED (tc=25):	7200lm
Beam Angle:	120°
Lens (Diffuser):	PC Opal
Dimming:	None
System Voltage [V]:	230V 50Hz
Connection:	Terminalx2
Mounting:	Surface, Suspended
Lifetime [h]:	L80B10: 100 000h
Lumen/W:	156lm/W
MacAdam (SDCM):	3
Through-wiring (mm2):	5x2,5
Color:	Grey
Length [mm]:	1536mm
Height [mm]:	80mm
Width [mm]:	76mm
Emergency light [h]:	3 hours
Emergency light testing:	Selftest
Emergency lumen out [lm]:	270lm

Stream Y Emergency version with 3h emergency light and selftest. Sealed industrial light fixture for ceiling surface mounting or pending down with wires, indoor and outdoor. The Stream is classified in accordance with IP65. The light fixture is made from robust fiber glass and is equipped with a milky white (opal) diffuser w/stripe. The Stream is prepared for cable 5x2,5mm2 wiring through for an efficient installation. Stream Y is a sealed industrial light fixture for ceiling surface mounting or pending down with wires, indoor and outdoor. The Stream is classified in accordance with IP65. The light fixture is made from robust fiber glass and is equipped with a milky white (opal) diffuser w/stripe. The Stream is prepared for cable 5x2,5mm2 wiring through for an efficient installation.