




PRODUCT FAMILY SHEET

Celestial Plafond



Celestial Plafond

Dimmable surface mounted ceiling light with PC diffuser and even light output. IP54 waterproof structural design, its an ideal replacement for wet locations. Comes with a switch option between 2700K(default)and 3000K. Dimmable by phasecut or DALI2. QuickConnect for easy installation.

VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
101575-120-3- ddd	25	2900	2750	2700-3000K	120°	Opal	80	White	LI, DALI2, Pu	QuickConnect
101571-120-3- ddd	18	2100	1913	2700-3000K	120°	Opal	80	White	LI, DALI2, Pu	QuickConnect
101571-120-3-p	18	2100	1913	2700-3000K	120°	Opal	80	White	Phase-Cut	QuickConnect
101570-120-3-p	12	1500	1350	2700-3000K	120°	Opal	80	White	Phase-Cut	QuickConnect
101575-E-S-12 0-3	25	2900	2750	2700-3000K	120°	Opal	80	White	Sensor (MW)	QuickConnect
101575-S-120-3	25	2900	2750	2700-3000K	120°	Opal	80	White	Sensor (MW)	QuickConnect