



PRODUCT SHEET

Universal G2 IP44 Base

Art. no: 102471-105-3



Universal G2 IP44 Base



Universal is an elegant and splash-proof IP44 LED luminaire designed for interior and industrial use. It features easy installation with pass-through wiring, low glare, and up to 150lm/W efficiency. The luminaire comes with a DIP switch, allowing you to customize the power level as needed, and the Kelvin can be adjusted between 3000K and 4000K. Available in lengths of 600mm, 1200mm, and 1500mm in on/off, sensor (Microwave), or DALI version. This product is also available with a microwave sensor with wireless communication between luminaires, using the Norlux Wireless Connect system for control.



SPECIFICATIONS

Lightsource Type:	LED (replaceable)
System Power [W]:	20/16/13/11W
CCT (Color Temperature):	3000-4000K
CRI / Ra:	80
Lumen Output:	2950lm
Lumen LED (tc=25):	3200lm
Beam Angle:	105°
Lens (Diffuser):	Opal
Dimming:	None
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	QuickConnect
Mounting:	Surface, Ceiling
Lifetime [h]:	L80B10: 100 000h
UGR (<=):	22
MacAdam (SDCM):	3
Through-wiring (mm2):	5x2,5
Color:	White
Length [mm]:	600mm
Height [mm]:	52mm
Width [mm]:	156mm
Weight [kg]:	1,43kg