




## FDV SPEC SHEET

Ceto Fixed

Art. no: 28830-2-01-36-3



92mm



## Ceto Fixed



Art. no: 28830-2-01-36-3

### LIGHT TECHNICAL

|                          |       |
|--------------------------|-------|
| Lumen Output:            | 1426  |
| Lumen LED (tc=25):       | 1500  |
| Beam Angle:              | 36°   |
| CCT (Color Temperature): | 3000  |
| CRI / Ra:                | 80    |
| Color Code:              | 830   |
| MacAdam (SDCM):          | 3     |
| Lens (Diffuser):         | Clear |

### MOUNTING / CONNECTION

|               |                     |
|---------------|---------------------|
| Connection:   | Depending on driver |
| Cut-out [mm]: | Ø92                 |
| Mounting:     | Recessed, Ceiling   |

### ELECTRICAL DATA

|                                      |                     |
|--------------------------------------|---------------------|
| Dimming:                             | Depending on Driver |
| System Power [W]:                    | 15                  |
| System Voltage [V]:                  | 230V 50Hz           |
| Protection Class:                    | 2                   |
| Max load pr circuit - B10:           | 35                  |
| Max load pr circuit - B16:           | 56                  |
| Max load pr circuit - C10:           | 74                  |
| Max load pr circuit - C16:           | 118                 |
| Leakage current [mA]:                | 5                   |
| Inrush current I <sub>max</sub> [A]: | 5                   |
| Inrush current time [µs]:            | 300                 |
| Socket / Cap-Base:                   | N/A                 |
| Current Output [mA]:                 | 350                 |
| Voltage Forward Min [V]:             | 32,4                |
| Voltage Forward Max [V]:             | 36                  |



## FDV SPEC SHEET

Ceto Fixed

Art. no: 28830-2-01-36-3



### PRODUCT

|                               |                 |
|-------------------------------|-----------------|
| To be recessed in insulation: | No              |
| Ingress Protection:           | IP44            |
| Impact Protection:            | IK02            |
| Operating Temperature [°C]:   | -20 - 45        |
| Lifetime [h]:                 | L80B10: 100 000 |
| Color:                        | White           |
| Height [mm]:                  | 90              |
| Diameter [mm]:                | 98              |
| Weight [kg]:                  | 0,35            |
| Housing Material :            | Aluminium       |
| Diffuser Material:            | Aluminium       |
| Material 2:                   | Polycarbonate   |
| Housing Material :            | Aluminium       |
| Diffuser Material:            | Aluminium       |
| Material 2:                   | Polycarbonate   |