



FDV SPEC SHEET

Arke Bollard

Art. no: 101150-01-10-900-1



Lighting Solutions



Arke Bollard



Art. no: 101150-01-10-900-1

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 865 |
| Lumen LED (tc=25): | 890 |
| CCT (Color Temperature): | 3000 |
| CRI / Ra: | 80 |
| Lens (Diffuser): | Clear |

MOUNTING / CONNECTION

| | |
|-------------|--------------|
| Connection: | QuickConnect |
| Mounting: | Bollard |

ELECTRICAL DATA

| | |
|--------------------------------------|-----------|
| Dimming: | None |
| System Power [W]: | 10 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |
| Max load pr circuit - B10: | 12 |
| Max load pr circuit - B16: | 19 |
| Max load pr circuit - C10: | 20 |
| Max load pr circuit - C16: | 32 |
| Leakage current [mA]: | 0,75 |
| Inrush current I _{max} [A]: | 50 |
| Inrush current time [µs]: | 157 |



FDV SPEC SHEET

Arke Bollard

Art. no: 101150-01-10-900-1



Lighting Solutions

PRODUCT

| | |
|------------------------------|-------------------------|
| Ingress Protection: | IP66 |
| Impact Protection: | IK10 |
| Corrosion Class: | C3 |
| Wind force (EPA) [m2] at 0°: | 0,178 |
| Surge Protection: | L/N-PE = 2KV, L-N = 2KV |
| Operating Temperature [°C]: | -30 - 50 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | Grey |
| RAL: | RAL7022 |
| Height [mm]: | 900 |
| Width [mm]: | 165 |
| Weight [kg]: | 7 |
| Housing Material : | Aluminium |