




## FDV SPEC SHEET

Leila C Maxi Surface

Art. no: 101375-70-2-ddd



Lighting Solutions



# Leila C Maxi Surface



Art. no: 101375-70-2-ddd

### LIGHT TECHNICAL

|                          |       |
|--------------------------|-------|
| Lumen Output:            | 5731  |
| Lumen LED (tc=25):       | 7200  |
| Beam Angle:              | 70°   |
| CCT (Color Temperature): | 3000  |
| CRI / Ra:                | 80    |
| Color Code:              | 830   |
| MacAdam (SDCM):          | 3     |
| Lens (Diffuser):         | Clear |

### MOUNTING / CONNECTION

|             |                  |
|-------------|------------------|
| Connection: | QuickConnect     |
| Mounting:   | Surface, Ceiling |

### ELECTRICAL DATA

|                                      |                      |
|--------------------------------------|----------------------|
| Dimming:                             | DALI                 |
| Dimming Output Type:                 | Amplitude Modulation |
| System Power [W]:                    | 48                   |
| System Voltage [V]:                  | 230V 50Hz            |
| Protection Class:                    | 1                    |
| Max load pr circuit - B10:           | 12                   |
| Max load pr circuit - B16:           | 20                   |
| Max load pr circuit - C10:           | 20                   |
| Max load pr circuit - C16:           | 34                   |
| Leakage current [mA]:                | 0,5                  |
| Inrush current I <sub>max</sub> [A]: | 30                   |
| Inrush current time [µs]:            | 200                  |
| Socket / Cap-Base:                   | N/A                  |
| Current Output [mA]:                 | 1200                 |
| Voltage Forward Min [V]:             | 30,6                 |
| Voltage Forward Max [V]:             | 39,3                 |



## FDV SPEC SHEET

Leila C Maxi Surface

Art. no: 101375-70-2-ddd



*Lighting Solutions*

### PRODUCT

|                               |                |
|-------------------------------|----------------|
| To be recessed in insulation: | No             |
| Ingress Protection:           | IP20           |
| Impact Protection:            | IK00           |
| Operating Temperature [°C]:   | -25 - 50       |
| Lifetime [h]:                 | L80B10: 60 000 |
| Color:                        | Black          |
| Height [mm]:                  | 150            |
| Width [mm]:                   | 230            |
| Weight [kg]:                  | 2,6            |