



**FDV SPEC SHEET**  
Halo Pendant Dimmable  
Art. no: 1129-2-120-9



## Halo Pendant Dimmable



Art. no: 1129-2-120-9

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2500
Lumen LED (tc=25):	6100
Beam Angle:	120
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	6
Lens (Diffuser):	Frosted
UGR (<=):	16

### MOUNTING / CONNECTION

Connection:	18i3 Quick connection
Mounting:	Ceiling, Pendant

### ELECTRICAL DATA

Dimming:	Phase-Cut
Dimming Output Type:	Amplitude Modulation
Dimming Phasecut Type:	Leading / Trailing edge
Flicker metric (Pst LM) <:	1
Stroboscopic effect metric (SVM) <	0,4
System Power [W]:	53
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	31
Max load pr circuit - B16:	50
Max load pr circuit - C10:	31
Max load pr circuit - C16:	50
Inrush current Imax [A]:	5
Inrush current time [μs]:	100
Voltage Forward Min [V]:	2,6
Voltage Forward Max [V]:	3,4



## FDV SPEC SHEET

Halo Pendant Dimmable  
Art. no: 1129-2-120-9



PRODUCT	
Ingress Protection:	IP20
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80B10: 50.000
Color:	Gold/White
Height [mm]:	34
Width [mm]:	1500