




FDV SPEC SHEET

Poseidon 2

Art. no: 6990-01-3-ddd



Poseidon 2



A⁺

Art. no: 6990-01-3-ddd

LIGHT TECHNICAL

Lumen Output:	1415
Lumen LED (tc=25):	1 500
Beam Angle:	120
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Opal
UGR (<=):	19

MOUNTING / CONNECTION

Mounting:	Surface, Ceiling
-----------	------------------

PRODUCT

Ingress Protection:	IP44
Impact Protection:	IK02
Lifetime [h]:	L80B10: 100 000
Color:	White
Length [mm]:	600
Height [mm]:	60
Width [mm]:	50
Weight [kg]:	0.9

ELECTRICAL DATA

Dimming:	DALI2
System Power [W]:	18
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	43
Max load pr circuit - B16:	68
Max load pr circuit - C10:	45
Max load pr circuit - C16:	73
Leakage current [mA]:	0,7
Inrush current I _{max} [A]:	7,48
Inrush current time [μs]:	194
Socket / Cap-Base:	N/A