



## FDV SPEC SHEET

Poseidon 2

Art. no: 6991-01-3-ddd



# Poseidon 2



A<sup>+</sup>

Art. no: 6991-01-3-ddd

### LIGHT TECHNICAL

Lumen LED (tc=25):	2 300
Beam Angle:	120
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Opal
UGR (<=):	19

### MOUNTING / CONNECTION

Mounting:	Surface, Ceiling
-----------	------------------

### PRODUCT

Ingress Protection:	IP44
Impact Protection:	IK02
Lifetime [h]:	L80B10: 100 000
Color:	White
Length [mm]:	900
Height [mm]:	60
Width [mm]:	50
Weight [kg]:	1,3

### ELECTRICAL DATA

Dimming:	DALI2
System Power [W]:	26
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	43
Max load pr circuit - B16:	68
Max load pr circuit - C10:	45
Max load pr circuit - C16:	73
Leakage current [mA]:	0,7
Inrush current I <sub>max</sub> [A]:	7,48
Inrush current time [μs]:	194
Socket / Cap-Base:	N/A