



FDV SPEC SHEET

Zoom Mini Spotlight

Art. no: 7063-02-560-2-ddd



Lighting Solutions



Zoom Mini Spotlight



Art. no: 7063-02-560-2-ddd

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen LED (tc=25): | 1250 |
| Beam Angle: | 5°-60° |
| CCT (Color Temperature): | 2700 |
| CRI / Ra: | 90 |
| Color Code: | 927 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Clear |

MOUNTING / CONNECTION

| | |
|-------------|-----------------|
| Connection: | Track 3-Circuit |
| Mounting: | Track, Ceiling |

PRODUCT

| | |
|---------------------|-----------------|
| Ingress Protection: | IP20 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | Black |
| Length [mm]: | 261 |
| Width [mm]: | 60 |
| Weight [kg]: | 0,95 |

ELECTRICAL DATA

| | |
|--------------------------------------|----------------------|
| Dimming: | DALI2 |
| Flicker metric (Pst LM) <: | 1 |
| Stroboscopic effect metric (SVM) <: | 0,4 |
| System Power [W]: | 15 |
| System Voltage [V]: | 230V 50Hz |
| Dimming Output Type: | Amplitude Modulation |
| Protection Class: | 1 |
| Max load pr circuit - B10: | 25 |
| Max load pr circuit - B16: | 40 |
| Max load pr circuit - C10: | 37 |
| Max load pr circuit - C16: | 60 |
| Leakage current [mA]: | 0,7 |
| Inrush current I _{max} [A]: | 30 |
| Inrush current time [μs]: | 100 |
| Current Output [mA]: | 500 |
| Voltage Forward Min [V]: | 34,2 |
| Voltage Forward Max [V]: | 37,7 |