



FDV SPEC SHEET

Galactic C

Art. no: 9057-4-02-3-ddd



Lighting Solutions



Galactic C



Art. no: 9057-4-02-3-ddd

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 3300 |
| Lumen LED (tc=25): | 4200 |
| Beam Angle: | 85° |
| CCT (Color Temperature): | 2700-3000K |
| CRI / Ra: | 90 |
| Color Code: | 927/930 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Micropris. |

MOUNTING / CONNECTION

| | |
|---------------|------------------------------------|
| Connection: | Terminal |
| Cut-out [mm]: | 220-250 |
| Mounting: | Partial-recessed, Surface, Pendant |

ELECTRICAL DATA

| | |
|------------------------------------|----------------------|
| Dimming: | DALI |
| Dimming Output Type: | Amplitude Modulation |
| Flickerfree: | Yes |
| Standby power Psb (W) <: | 0,5 |
| Flicker metric (Pst LM) <: | 1 |
| Stroboscopic effect metric (SVM) < | 0,4 |
| System Power [W]: | 40 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |
| Max load pr circuit - B10: | 22 |
| Max load pr circuit - B16: | 35 |
| Max load pr circuit - C10: | 22 |
| Max load pr circuit - C16: | 35 |
| Leakage current [mA]: | 0,7 |
| Inrush current Imax [A]: | 20 |
| Inrush current time [µs]: | 120 |
| Socket / Cap-Base: | N/A |
| Current Output [mA]: | 1050mA |



FDV SPEC SHEET

Galactic C

Art. no: 9057-4-02-3-ddd



Lighting Solutions

PRODUCT

| | |
|-----------------------------|-----------------|
| Ingress Protection: | IP40 |
| Impact Protection: | IK03 |
| Operating Temperature [°C]: | -20 - 40 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | White |
| RAL: | RAL9016 |
| Length [mm]: | 400 |
| Height [mm]: | 102 |
| Width [mm]: | 400 |
| Diameter [mm]: | 400 |
| Weight [kg]: | 2,85 |
| Housing Material : | Aluminium 6063 |
| Diffuser Material: | Polycarbonate |
| Material 2: | SPCC |