



FDV SPEC SHEET

Galactic C

Art. no: 9077-3-02-2-ddd



Galactic C



Art. no: 9077-3-02-2-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen LED (tc=25):	7800
Beam Angle:	120°
CCT (Color Temperature):	2700-3000K
CRI / Ra:	80
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.

MOUNTING / CONNECTION

Connection:	QuickConnect
Cut-out [mm]:	Ø385-Ø415
Mounting:	Partial-recessed, Surface, Pendant

ELECTRICAL DATA

Dimming:	CLO, DALI2, Push
Dimming Output Type:	AM+PWM
System Power [W]:	80
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	7
Max load pr circuit - B16:	12
Max load pr circuit - C10:	12
Max load pr circuit - C16:	20
Inrush current I _{max} [A]:	46
Inrush current time [µs]:	240
Socket / Cap-Base:	N/A
Current Output [mA]:	550



FDV SPEC SHEET

Galactic C

Art. no: 9077-3-02-2-ddd



Lighting Solutions

PRODUCT

Ingress Protection:	IP40
Operating Temperature [°C]:	-20 - 45
Lifetime [h]:	L80B10: 100 000
Color:	Black
RAL:	RAL9005
Height [mm]:	86
Width [mm]:	800
Weight [kg]:	11
Housing Material :	Aluminium