



FDV SPEC SHEET

Galactic C

Art. no: 9085-2-02-2-ddd



Galactic C



Art. no: 9085-2-02-2-ddd

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen LED (tc=25): | 9000 |
| Beam Angle: | 120° |
| CCT (Color Temperature): | 2700-3000K |
| CRI / Ra: | 80 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Micropris. |

MOUNTING / CONNECTION

| | |
|---------------|------------------------------------|
| Connection: | QuickConnect |
| Cut-out [mm]: | Ø385-Ø415 |
| Mounting: | Partial-recessed, Surface, Pendant |

PRODUCT

| | |
|-----------------------------|-----------------|
| Ingress Protection: | IP40 |
| Operating Temperature [°C]: | -20 - 45 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | Black |
| RAL: | RAL9005 |
| Height [mm]: | 86 |
| Width [mm]: | 1000 |
| Weight [kg]: | 16 |

ELECTRICAL DATA

| | |
|----------------------|-----------|
| Dimming: | DALI2 |
| System Power [W]: | 100 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |
| Socket / Cap-Base: | N/A |
| Current Output [mA]: | 700 |