




PRODUCT FAMILY SHEET

Z line



Lighting Solutions



Z line

Z Line is an LED fixture designed with a focus on energy savings and efficient installation. It utilizes the latest LED technology, providing up to 180 lm/W. The fixture features a 2,5mm² throughwiring and quick connections on both ends, making installation simple and fast without the need to open the fixture. The fixture is made of galvanized steel and is available in two lengths; 1420mm with 42W in 3000K and 4000K, 1700mm with 42W and 72W in 3000K and 4000K. All versions can be ordered with DALI2.

VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
102086-00-1	42	8000	7630	4000	70°	Lens	80	Steel	None	QuickConnect
102083-00-1	74	13500	13040	3000	70°	Lens	80	Steel	None	QuickConnect
102083-01-1	74	13500	12970	3000	90°	Lens	80	Steel	None	QuickConnect
102086-01-1	42	8000	7600	4000	90°	Lens	80	Steel	None	QuickConnect
102088-00-1	74	14200	13580	4000	70°	Lens	80	Steel	None	QuickConnect
102088-01-1	74	14200	13515	4000	90°	Lens	80	Steel	None	QuickConnect
102081-00-1	42	7600	7320	3000	70°	Lens	80	Steel	None	QuickConnect
102081-01-1	42	7600	7300	3000	90°	Lens	80	Steel	None	QuickConnect
102087-00-1	42	8200	7880	4000	70°	Lens	80	Steel	None	QuickConnect
102082-01-1	42	7800	7613	3000	90°	Lens	80	Steel	None	QuickConnect
102088-01-1-d dd	74	14200	13515	4000	90°	Lens	80	Steel	DALI2	QuickConnect
102083-00-1-d dd	74	13500	13040	3000	70°	Lens	80	Steel	DALI2	QuickConnect
102086-01-1-d dd	42	8000	7660	4000	90°	Lens	80	Steel	DALI2	QuickConnect
102087-00-1-d dd	42	8200	7880	4000	70°	Lens	80	Steel	DALI2	QuickConnect
102088-00-1-d dd	74	14200	13580	4000	70°	Lens	80	Steel	DALI2	QuickConnect