




FDV SPEC SHEET
Leila C Mini Surface
Art. no: 101360-70-2-ddd

Ledpro
by NORLUX



Leila C Mini Surface



Art. no: 101360-70-2-ddd

LYS TEKNISK

Lumen ut (lm):	2715
Lumen LED (tc=25):	3000
Spredningsvinkel [°]:	70°
Fargetemperatur [K]:	3000
Fargegjengivelse [CRI/Ra]:	80
Fargekode:	830
Fargetoleranse [SDCM]:	3
Optikk:	Klar

MONTERING / TILKOBLING

Tilkobling:	Hurtigkobling
Montering:	Utenpåliggende, Tak

ELEKTRISK DATA

Dimmetype:	DALI
Dimming Output Type:	Amplitude Modulation
Systemeffekt [W]:	20
Spenning [V]:	230V 50Hz
Isolasjonsklasse:	1
Belastning pr kurs - B10:	40
Belastning pr kurs - B16:	80
Belastning pr kurs - C10:	50
Belastning pr kurs - C16:	136
Startstrøm I _{max} [A]:	20
Startstrøm tid [µs]:	50
Sokkel :	N/A
Strøm LED [mA]:	500



FDV SPEC SHEET

Leila C Mini Surface

Art. no: 101360-70-2-ddd



PRODUKT

Monteres rett i isolasjon:	No
IP-grad:	IP20
Vandal klasse:	IK00
Driftstemperatur [°C]:	-25 - 50
Forventet Levetid :	L80B10: 60 000
Farge :	Sort
Høyde [mm]:	150
Bredde [mm]:	140
Vekt [kg]:	1