





## FDV SPEC SHEET

Leila C Mini Surface

Art. no: 101360-70-3



Lighting Solutions



# Leila C Mini Surface



Art. no: 101360-70-3

### LIGHT TECHNICAL

Lumen Output:	2715
Lumen LED (tc=25):	3000
Beam Angle:	70°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

### MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Surface, Ceiling

### ELECTRICAL DATA

Dimming:	None
System Power [W]:	20
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	65
Max load pr circuit - B16:	100
Max load pr circuit - C10:	65
Max load pr circuit - C16:	100
Inrush current I <sub>max</sub> [A]:	8
Inrush current time [µs]:	80
Socket / Cap-Base:	N/A
Current Output [mA]:	500



## FDV SPEC SHEET

Leila C Mini Surface

Art. no: 101360-70-3



*Lighting Solutions*

### PRODUCT

To be recessed in insulation:	No
Ingress Protection:	IP20
Impact Protection:	IK00
Operating Temperature [°C]:	-25 - 50
Lifetime [h]:	L80B10: 60 000
Color:	White
Height [mm]:	150
Width [mm]:	140
Weight [kg]:	1