



## FDV SPEC SHEET

Montana S


Art. no: 103023-30-BV-1



*Lighting Solutions*



# Montana S



Art. no: 103023-30-BV-1

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	4200
Lumen LED (tc=25):	4620
Beam Angle:	143°*65°
CCT (Color Temperature):	3000K/2200K
CRI / Ra:	70
Color Code:	730/722
MacAdam (SDCM):	6
Lens (Diffuser):	PMMA

### MOUNTING / CONNECTION

Connection:	Cable 6m
Cut-out [mm]:	n/a
Mounting:	Mast Ø60-76



## FDV SPEC SHEET

Montana S

Art. no: 103023-30-BV-1



*Lighting Solutions*

PRODUCT		ELECTRICAL DATA	
Ingress Protection:	IP66	Dimming:	DALI2, D4i
Impact Protection:	IK08	Flickerfree:	Yes
Corrosion Class:	C4	Standby power Psb (W) <:	0,5
Wind force (EPA) [m2] at 0°:	0,11	Flicker metric (Pst LM) <:	0,007
Surge Protection:	L_N = 10KV	Stroboscopic effect metric (SVM) <	0,005
Operating Temperature [°C]:	-40 - 50	System Power [W]:	30
Lifetime [h]:	L80B10: 100 000	System Voltage [V]:	230V 50Hz
Color:	Grey	Protection Class:	2
RAL:	Pantone8403C	Max load pr circuit - B10:	4
Length [mm]:	574	Max load pr circuit - B16:	7
Height [mm]:	124	Max load pr circuit - C10:	8
Width [mm]:	219	Max load pr circuit - C16:	12
Diameter [mm]:	76	Leakage current [mA]:	0,7
Weight [kg]:	4,9	Inrush current Imax [A]:	46,4
Housing Material :	Aluminium	Inrush current time [µs]:	352
Diffuser Material:	PMMA	Socket / Cap-Base:	Zhaga
Material 2:	Driver	Current Output [mA]:	64.2
		Voltage Forward Min [V]:	21,7
		Voltage Forward Max [V]:	22,2
		Emergency light [h]:	No Emergency light