



Montana M



Montana feature an innovative, tool-free system that allows for easy replacement of the electrical compartment directly on-site. This ensures fast and efficient maintenance while significantly reducing labor costs and downtime. The sleek and aerodynamic design minimizes wind resistance, enhances reliability, and optimizes heat dissipation, resulting in an extended lifespan. Built to withstand challenging conditions such as Nordic roads and high-altitude environments, Montana deliver dependable performance even in extreme settings.



Lightsource Type:LED (built in)System Power [W]:60WCCT (Color Temperature):3000KCRI / Ra:70Lumen Output:8400lmLumen LED (tc=25):9240lmBeam Angle:143°*65°Lens (Diffuser):PMMADimming:0AL12, D4iFlickerfree:YesSystem Voltage [V]:Cable 8mMounting:Mast
CCT (Color Temperature):3000KCRI / Ra:70Lumen Output:8400lmLumen LED (tc=25):9240lmBeam Angle:143°*65°Lens (Diffuser):PMMADimming:DALl2, D4iFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Cable 8mMounting:Mast
CRI / Ra:70Lumen Output:8400lmLumen LED (tc=25):9240lmBeam Angle:143°*65°Lens (Diffuser):PMMADimming:DAL12, D4iFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Cable 8mMounting:Mast
Lumen Output:8400lmLumen LED (tc=25):9240lmBeam Angle:143°*65°Lens (Diffuser):PMMADimming:DAL12, D4iFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Cable 8mMounting:Mast
Lumen LED (tc=25):9240lmBeam Angle:143°*65°Lens (Diffuser):PMMADimming:DAL12, D4iFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Cable 8mMounting:Mast
Beam Angle:143°*65°Lens (Diffuser):PMMADimming:DAL12, D4iFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Cable 8mMounting:Mast
Lens (Diffuser):PMMADimming:DAL12, D4iFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Cable 8mMounting:Mast
Dimming:DAL12, D4iFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Cable 8mMounting:Mast
Flickerfree:YesSystem Voltage [V]:230V 50HzConnection:Cable 8mMounting:Mast
System Voltage [V]:230V 50HzConnection:Cable 8mMounting:Mast
Connection: Cable 8m Mounting: Mast
Mounting: Mast
0
Cut-out [mm]: n/amm
Lifetime [h]: L80B10: 100 000h
Lumen/W: 140lm/W
MacAdam (SDCM): 5
Color: Grey
Length [mm]: 665mm
Height [mm]: 125mm
Width [mm]: 250mm
Diameter [mm]: 76mm
Weight [kg]: 6,2kg
Emergency light [h]: No Emergency light
Emergency light testing: N/A