




Book Pole-Top Maxi 840 1x36W Ø60mm adapter RAL7



This square pole-top mounted floodlight is designed for outdoor installation on poles with diameters of either 60 mm. Constructed from phospho-chromatised and polyester powder-coated die-cast copper-free aluminum, it ensures durability and resilience against outdoor conditions. The floodlight features tempered safety glass, a moulded silicone gasket, and stainless steel screws for added protection. Included is a versatile flange suitable for pole diameters of 60 mm or 76 mm, providing flexibility in installation. The illumination is powered by 12 or 24 CREE XP-G2 LEDs known for their efficiency and brightness. The built-in LED driver operates on 220-240V and 50-60Hz, streamlining the installation process. With an IP65 rating, this floodlight offers high-level protection against dust and water, making it ideal for diverse outdoor applications, such as lighting up parking lots, pathways, or any outdoor space requiring effective illumination.

IP65	230V 50Hz

Г

SPECIFICATIONS

System Power [W]:	36W
CCT (Color Temperature):	4000K
CRI / Ra:	80
Dimming:	None
System Voltage [V]:	230V 50Hz
Connection:	Cable 5m
Mounting:	Mast
Color:	Dark Grey
Length [mm]:	445mm
Height [mm]:	43mm
Width [mm]:	212mm
Weight [kg]:	3kg