



## PRODUCT FAMILY SHEET

Celestial Plafond



# Celestial Plafond

Dimmable surface mounted ceiling light with PC diffuser and even light output. IP54 waterproof structural design, its an ideal replacement for wet locations. Comes with a switch option between 2700K(default)and 3000K. Dimmable by phasecut or DALI2. QuickConnect for easy installation.

## VERSIONS

Art.No	Effect [W]	Cold Lumen [lm]	Lumen Output [lm]	CCT [K]	Beam Angle [°]	Lens Difuser	CRI [>]	Color	Light Control	Connection
101575-120-3- ddd	25	2900	2750	2700-3000K	120°	Opal	80	White	LI, DALI2, Pu	QuickConnect
101571-120-3- ddd	18	2100	1913	2700-3000K	120°	Opal	80	White	LI, DALI2, Pu	QuickConnect
101571-120-3-p	18	2100	1913	2700-3000K	120°	Opal	80	White	Phase-Cut	QuickConnect
101570-120-3-p	12	1500	1350	2700-3000K	120°	Opal	80	White	Phase-Cut	QuickConnect
101575-E-S-12 0-3	25	2900	2750	2700-3000K	120°	Opal	80	White	Sensor (MW)	QuickConnect
101575-S-120-3	25	2900	2750	2700-3000K	120°	Opal	80	White	Sensor (MW)	QuickConnect