



## LED Strip SOB 13W/m



The Led Strip SOB provides perfectly even and pleasant light without visible dots or spots, creating an atmosphere that is both inviting and functional. The LED strip boasts high lumens per watt, allowing for flexible installation so you can customize the lighting according to your needs and preferences. With 3-step MacAdam color consistency, you can be confident that our light remains stable and uniform over time. Choose between 2700K, 3000K, or 4000K. This LED strip has a beam angle of 150° and CRI 90, rendering colors in a natural and accurate manner. Choose between IP20 or IP65 variants for both indoor and outdoor use.

## 

CCT (Color Temperature):3000KCRI / Ra:90Color Code:930Lumen Output [lm/ m]:1690lm/mEfficiacy [lm/ W]:110lm/wMacAdam (SDCM):3Beam Angle:150°LED pr. meter:288System Voltage [V]:24VDCSystem Power [W/m]:13Dimming:Depending on DriverMounting:Adhesive tapeHeat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmIngress Protection:P65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mmWidth:Smm	SPECIFICATIONS	
Color Code:930Lumen Output [lm/ m]:1690lm/mEfficiacy [lm/ W]:110lm/wMacAdam (SDCM):3Beam Angle:150°LED pr. meter:288System Voltage [V]:24VDCSystem Power [W/m]:13Dimming:Depending on DriverMounting:Adhesive tapeHeat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmMax. length [m]:50 000hLifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mmWidth:Smm	CCT (Color Temperature):	3000K
Lumen Output [lm/ m]:1690lm/mEfficiacy [lm/ W]:1690lm/mMacAdam (SDCM):3Beam Angle:150°LED pr. meter:288System Voltage [V]:24VDCSystem Power [W/m]:13Dimming:Depending on DriverMounting:Adhesive tapeHeat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmIngress Protection:P65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mmWidth:Smm	CRI / Ra:	90
Efficiacy [lm/ W]:110lm/wMacAdam (SDCM):3Beam Angle:150°LED pr. meter:288System Voltage [V]:24VDCSystem Power [W/m]:13Dimming:Depending on DriverMounting:Adhesive tapeHeat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmMax. length [m]:50Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mm	Color Code:	930
MacAdam (SDCM):3Beam Angle:150°LED pr. meter:288System Voltage [V]:24VDCSystem Power [W/m]:13Dimming:Depending on DriverMounting:Adhesive tapeHeat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmMax. length [m]:5000mLifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mm	Lumen Output [lm/ m]:	1690lm/m
Beam Angle:150°BEam Angle:150°LED pr. meter:288System Voltage [V]:24VDCSystem Power [W/m]:13Dimming:Depending on DriverMounting:Adhesive tapeHeat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmMax. length [m]:50 000hLifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mm	Efficiacy [lm/ W]:	110lm/w
LED pr. meter:288System Voltage [V]:24VDCSystem Power [W/m]:13Dimming:Depending on DriverMounting:Adhesive tapeHeat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmMax. length [m]:SmIngress Protection:IP65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:00mm	MacAdam (SDCM):	3
System Voltage [V]:24VDCSystem Power [W/m]:13Dimming:Depending on DriverMounting:Adhesive tapeHeat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmMax. length [m]:5mIngress Protection:IP65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mm	Beam Angle:	150°
System Power [W/m]:13Dimming:Depending on DriverMounting:Adhesive tapeHeat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmMax. length [m]:5mIngress Protection:IP65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mmWidth:5mm	LED pr. meter:	288
Dimming:Depending on DriverMounting:Adhesive tapeHeat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmMax. length [m]:SmIngress Protection:IP65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mmWidth:Smm	System Voltage [V]:	24VDC
Mounting:Adhesive tapeHeat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmMax. length [m]:5mIngress Protection:IP65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mmWidth:5mm	System Power [W/m]:	13
Heat sink needed:NoConnection:Cable 2mCuttable [mm]:55.56mmMax. length [m]:5mIngress Protection:IP65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mmWidth:5mm	Dimming:	Depending on Driver
Connection:Cable 2mCuttable [mm]:55.56mmMax. length [m]:5mIngress Protection:IP65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mmWidth:5mm	Mounting:	Adhesive tape
Cuttable [mm]:55.56mmMax. length [m]:5mIngress Protection:IP65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mmWidth:5mm	Heat sink needed:	No
Max. length [m]:5mIngress Protection:IP65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mmWidth:5mm	Connection:	Cable 2m
Ingress Protection:IP65Lifetime [h]:50 000hColor:WhiteLength:5000mmHeight:10mmWidth:5mm	Cuttable [mm]:	55.56mm
Lifetime [h]:     50 000h       Color:     White       Length:     5000mm       Height:     10mm       Width:     5mm	Max. length [m]:	5m
Color:WhiteLength:5000mmHeight:10mmWidth:5mm	Ingress Protection:	IP65
Length:5000mmHeight:10mmWidth:5mm	Lifetime [h]:	50 000h
Height: 10mm   Width: 5mm	Color:	White
Width: 5mm	Length:	5000mm
	Height:	10mm
Max width Led Strip : 8mm	Width:	5mm
	Max width Led Strip :	8mm