



FDV SPEC SHEET

Ufo T High Bay

Art. no: 102765-02-A-2

Ledpro
by **NORLUX**



Ufo T High Bay



Art. no: 102765-02-A-2

LYS TEKNISK

Lyskilde :	LED (innebygget)
Lumen ut (lm):	43200
Lumen LED (tc=25):	43200
Spredningsvinkel [°]:	105
Fargetemperatur [K]:	4000
Fargegjengivelse [CRI/Ra]:	80
Fargekode:	840
Fargetoleranse [SDCM]:	3
Optikk:	Klar
UGR (<=):	26



FDV SPEC SHEET

Ufo T High Bay

Art. no: 102765-02-A-2



PRODUKT		ELEKTRISK DATA	
IP-grad:	IP65	Dimmetype:	0-10V
Vandal klasse:	IK08	Dimming Output Type:	PWM
Korrosjonsklasse:	C3	Output Hz:	1000-3000(Hz)
Driftstemperatur [°C]:	-30 - 50	Dimming Phasecut Type:	Leading / Trailing edge
Forventet Levetid :	L80B10: 100 000	Flimmerfri:	Nei
Farge :	Sort	Standby power Psb (W) <:	0,5
RAL:	RAL9004	Flicker metric (Pst LM) <:	0,1
Lengde [mm]:	360	Stroboscopic effect metric (SVM) <	1
Høyde [mm]:	169	Systemeffekt [W]:	240/150/100
Bredde [mm]:	360	Spennning [V]:	230V 50Hz
Diameter [mm]:	360	Isolasjonsklasse:	1
Vekt [kg]:	2,4	Maks belastning pr kurs - B10:	5
Hoved Materiale:	Aluminium	Maks belastning pr kurs - B16:	8
Diffusere Materiale:	Polykarbonat	Maks belastning pr kurs - C10:	6
Materiale 2:	Mechanical installed part(Steel)	Maks belastning pr kurs - C16:	9
		Lekkasjestrøm [mA]:	5
		Startstrøm I _{max} [A]:	80
		Startstrøm tid [µs]:	350
		Strøm LED [mA]:	820
		Spennning LED Min [V]:	2,9
		Spennning LED Max [V]:	3
		Nødllys [t]:	Uten nødllys
		Nødllys testfunksjon:	N/A
MONTERING / TILKOBLING			
Tilkobling:		RST20i3 5m cable	
Montering:		Nedhengt, Vegg, Tak	