



FDV SPEC SHEET

T-Line Louvre

Art. no: 103120-60-2-ddd



T-Line Louvre



Art. no: 103120-60-2-ddd

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 8290 |
| Lumen LED (tc=25): | 9000 |
| Beam Angle: | 60° |
| CCT (Color Temperature): | 3000 |
| CRI / Ra: | 90 |
| Color Code: | 930 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Lens |
| UGR (<=): | 19 |

MOUNTING / CONNECTION

| | |
|-------------|---------------------|
| Connection: | Track 3-Circuit+dim |
| Mounting: | Track, Suspended |

ELECTRICAL DATA

| | |
|--------------------------------------|--------------|
| Dimming: | DALI |
| Dimming Phasecut Type: | Leading edge |
| Flickerfree: | Yes |
| System Power [W]: | 60-45 |
| Preset Power [W]: | 60 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |
| Max load pr circuit - B10: | 14 |
| Max load pr circuit - B16: | 22 |
| Max load pr circuit - C10: | 23 |
| Max load pr circuit - C16: | 37 |
| Inrush current I _{max} [A]: | 30 |
| Inrush current time [μs]: | 180 |
| Current Output [mA]: | 340 |



FDV SPEC SHEET

T-Line Louvre

Art. no: 103120-60-2-ddd



Lighting Solutions

PRODUCT

| | |
|-----------------------------|-----------------|
| Ingress Protection: | IP40 |
| Impact Protection: | IK03 |
| Operating Temperature [°C]: | -25 - 60 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | Black |
| RAL: | RAL9017 |
| Length [mm]: | 1493 |
| Height [mm]: | 58 |
| Width [mm]: | 62 |
| Weight [kg]: | 1,5 |
| Housing Material : | Steel |
| Diffuser Material: | PMMA |