



FDV SPEC SHEET

Poseidon 3

Art. no: 6991-2-01-2-ddd



Lighting Solutions



Poseidon 3



Art. no: 6991-2-01-2-ddd

LIGHT TECHNICAL

Lightsource Type:	LED (replaceable)
Lumen Output:	2691
Lumen LED (tc=25):	2800
Beam Angle:	142°
CCT (Color Temperature):	3000-4000K
Preset CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	930/940
MacAdam (SDCM):	3
Lens (Diffuser):	PC Opal

MOUNTING / CONNECTION

Connection:	Terminal
Mounting:	Surface



FDV SPEC SHEET

Poseidon 3

Art. no: 6991-2-01-2-ddd



Lighting Solutions

PRODUCT		ELECTRICAL DATA	
Ingress Protection:	IP44	Dimming:	DALI
Impact Protection:	IK07	Dimming Output Type:	Amplitude Modulation
Lifetime [h]:	L80B10: 100 000	Flickerfree:	Yes
Color:	Black	Standby power P _{sb} (W) <:	0,5
RAL:	RAL9006	Flicker metric (P _{st} LM) <:	0,009
Length [mm]:	900	Stroboscopic effect metric (SVM) <	0,003
Height [mm]:	60	System Power [W]:	27
Width [mm]:	60	Preset Power [W]:	27
Weight [kg]:	1,628	System Voltage [V]:	230V 50Hz
Housing Material :	Aluminium 6063	Protection Class:	1
Diffuser Material:	Polycarbonate	Max load pr circuit - B10:	52
		Max load pr circuit - B16:	83
		Max load pr circuit - C10:	52
		Max load pr circuit - C16:	83
		Leakage current [mA]:	0,61
		Inrush current I _{max} [A]:	7,1
		Inrush current time [μs]:	188
		Socket / Cap-Base:	N/A
		Current Output [mA]:	200
		Voltage Forward Min [V]:	2,8
		Voltage Forward Max [V]:	3,2
		Emergency light [h]:	No Emergency light