


Cylinder 60







CE	IP20	230V 50Hz	IK02	

SPECIFICATIONS

Lightsource Type:	LED (built in)		
System Power [W]:	15W		
CCT (Color Temperature):	2700К		
CRI / Ra:	90		
Lumen Output:	1400lm		
Lumen LED (tc=25):	2100lm		
Beam Angle:	36°		
Lens (Diffuser):	Clear		
Dimming:	Phase-Cut		
Flickerfree:	Yes		
System Voltage [V]:	230V 50Hz		
Connection:	Track 3-Circuit		
Mounting:	Track, Ceiling		
Lifetime [h]:	L80B10: 100 000h		
UGR (<=):	19		
Lumen/W:	100lm/W		
MacAdam (SDCM):	3		
Color:	Black		
Length [mm]:	130mm		
Height [mm]:	130mm		
Diameter [mm]:	60mm		
Weight [kg]:	0,39kg		
Emergency light [h]:	No Emergency light		

Cylinder 60 is an elegant and modern spotlight, designed to deliver high light output and exceptional color rendering in various environments. With a diameter of 60mm and length of 130mm, this spotlight is both discreet and efficient. Available with beam angles of 15°, 25°, or 36° and color temperatures of 2700K, 3000K, or Dim 2 Warm (3000-1800K). CRI90 ensures excellent color rendering. Equipped with phase-cut dimming. Made of powder-coated aluminum, Cylinder 60 is ideal for use in bedrooms, cafes, cabins, hotels, kitchens, and homes. The built-in driver in the sleek fixture housing provides a clean and modern appearance, while the spotlight can be tilted up to 90° and rotated 350° around its own axis for optimal adjustability. This makes Cylinder 60 perfect for both private and commercial environments.