



## PRODUCT SHEET

Trunk Line

Art. no: CFTL-1550-30NR-08-3

# NORLUX®

*Lighting Solutions*

## Trunk Line

Trunk Line is our new fixture within technical lighting. This product is composed of two luminaires: Trunk with the optics of the T-line. Trunk Line is 50W, but the brightness can be adjusted down to 35W, 40W or 45W using the DIP switch on the driver. Supplied in 3000K with 60° light spread. Choose between on/off or DALI version. Power level with DIP switch: 50W = 8500lm | 45W = 7850lm | 40W = 7100lm | 35W = 6325lm



### SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	50/45/40/35W
CCT (Color Temperature):	3000K
CRI / Ra:	80
Lumen Output:	8473lm
Lumen LED (tc=25):	9300lm
Beam Angle:	60
Lens (Diffuser):	Lens
Dimming:	None
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	Trunk 8-wires
Mounting:	Suspended, Ceiling
Lifetime [h]:	L80B10: 100 000h
Lumen/W:	174lm/W
UGR (<=):	19
Color:	White
Length [mm]:	1500mm