



FDV SPEC SHEET

Blume Vandal


Art. no: 102781-38-3



Lighting Solutions



Blume Vandal



Art. no: 102781-38-3

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 2400 |
| Lumen LED (tc=25): | 2760 |
| Beam Angle: | 38 |
| CCT (Color Temperature): | 3000 |
| CRI / Ra: | 80 |
| Color Code: | 830 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Lens |
| UGR (<=): | 19 |

MOUNTING / CONNECTION

| | |
|---------------|-------------------|
| Connection: | EPN0024 |
| Cut-out [mm]: | 200 |
| Mounting: | Recessed, Ceiling |

ELECTRICAL DATA

| | |
|--------------------------|---------------------|
| Dimming: | Depending on Driver |
| Flickerfree: | Yes |
| System Power [W]: | 25 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 2 |
| Socket / Cap-Base: | N/A |
| Current Output [mA]: | 540 |
| Voltage Forward Min [V]: | 33 |
| Voltage Forward Max [V]: | 38 |
| Emergency light [h]: | No Emergency light |
| Emergency light testing: | N/A |



FDV SPEC SHEET

Blume Vandal

Art. no: 102781-38-3



Lighting Solutions

PRODUCT

| | |
|-----------------------------|-----------------|
| Ingress Protection: | IP65 |
| Impact Protection: | IK10 |
| Operating Temperature [°C]: | -20 - 45 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | White |
| RAL: | RAL9016 |
| Length [mm]: | 235 |
| Height [mm]: | 81 |
| Width [mm]: | 235 |
| Diameter [mm]: | 235 |
| Weight [kg]: | 1,27 |
| Housing Material : | Aluminium |
| Diffuser Material: | Polycarbonate |
| Material 2: | Polycarbonate |