



FDV SPEC SHEET

Areto Kitchen

Art. no: 101333-01-3



Lighting Solutions



Areto Kitchen



Art. no: 101333-01-3

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	1287
Lumen LED (tc=25):	1600
Beam Angle:	120°
CCT (Color Temperature):	3000-4000K
CRI / Ra:	80
Color Code:	830/840
MacAdam (SDCM):	5
Lens (Diffuser):	PC Opal

MOUNTING / CONNECTION

Connection:	QuickConnect
Through-wiring (mm2):	3x2,5

ELECTRICAL DATA

Dimming:	None
Flicker metric (Pst LM) <:	0,05
Stroboscopic effect metric (SVM) <	0,049
System Power [W]:	13
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	37
Max load pr circuit - B16:	60
Max load pr circuit - C10:	62
Max load pr circuit - C16:	99
Leakage current [mA]:	0,2
Inrush current I _{max} [A]:	4,8
Inrush current time [µs]:	320
Voltage Forward Min [V]:	37
Voltage Forward Max [V]:	42



FDV SPEC SHEET

Areto Kitchen

Art. no: 101333-01-3



Lighting Solutions

PRODUCT

Ingress Protection:	IP20
Impact Protection:	IK09
Operating Temperature [°C]:	-10 - 40
Lifetime [h]:	L80B10: 100 000
Color:	White
RAL:	RAL9003
Length [mm]:	1100
Height [mm]:	51
Width [mm]:	68
Weight [kg]:	1,42
Housing Material :	Aluminium 6063