



FDV SPEC SHEET

Mika29 Bollard

Art. no: 102920-5



Lighting Solutions



Mika29 Bollard



Art. no: 102920-5

LIGHT TECHNICAL

Lightsource Type:	LED (replaceable)
Lumen Output:	1045
Lumen LED (tc=25):	1100
Beam Angle:	360°
CCT (Color Temperature):	4000
CRI / Ra:	80
Color Code:	840
MacAdam (SDCM):	6
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	Cable 1.5m
Mounting:	Bollard

ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
System Power [W]:	12
System Voltage [V]:	230V 50Hz
Protection Class:	2
Socket / Cap-Base:	N/A
Current Output [mA]:	350
Voltage Forward Min [V]:	5,8
Voltage Forward Max [V]:	6,6



FDV SPEC SHEET

Mika29 Bollard

Art. no: 102920-5



PRODUCT	
Ingress Protection:	IP65
Impact Protection:	IK08
Corrosion Class:	C4
Wind force (EPA) [m2] at 0°:	0,126
Operating Temperature [°C]:	-25 - 45
Lifetime [h]:	L80B10: 100 000
Color:	Antracite
RAL:	RAL7016
Height [mm]:	1000
Width [mm]:	170
Diameter [mm]:	217
Weight [kg]:	4
Housing Material :	Aluminium
Diffuser Material:	Polycarbonate
Material 2:	Iron galvanizing