



FDV SPEC SHEET
Ufo T High Bay
Art. no: 102765-02-2-ddd



Ufo T High Bay



Art. no: 102765-02-2-ddd

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 43200 |
| Lumen LED (tc=25): | 43200 |
| Beam Angle: | 105 |
| CCT (Color Temperature): | 4000 |
| CRI / Ra: | 80 |
| Color Code: | 840 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Clear |
| UGR (<=): | 26 |



FDV SPEC SHEET

Ufo T High Bay
Art. no: 102765-02-2-ddd



| PRODUCT | |
|-----------------------------|----------------------------------|
| Ingress Protection: | IP65 |
| Impact Protection: | IK08 |
| Corrosion Class: | C3 |
| Operating Temperature [°C]: | -30 - 50 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | Black |
| RAL: | RAL9004 |
| Length [mm]: | 360 |
| Height [mm]: | 169 |
| Width [mm]: | 360 |
| Diameter [mm]: | 360 |
| Weight [kg]: | 2,4 |
| Housing Material : | Aluminium |
| Diffuser Material: | Polycarbonate |
| Material 2: | Mechanical installed part(Steel) |

| ELECTRICAL DATA | |
|------------------------------------|--------------------|
| Dimming: | DALI |
| Flickerfree: | Yes |
| Standby power Psb (W) <: | 0,5 |
| Flicker metric (Pst LM) <: | 0,1 |
| Stroboscopic effect metric (SVM) < | 1 |
| System Power [W]: | 240 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 1 |
| Max load pr circuit - B10: | 5 |
| Max load pr circuit - B16: | 8 |
| Max load pr circuit - C10: | 6 |
| Max load pr circuit - C16: | 9 |
| Leakage current [mA]: | 5 |
| Inrush current Imax [A]: | 80 |
| Inrush current time [µs]: | 350 |
| Current Output [mA]: | 820 |
| Voltage Forward Min [V]: | 2,9 |
| Voltage Forward Max [V]: | 3 |
| Emergency light [h]: | No Emergency light |
| Emergency light testing: | N/A |

| MOUNTING / CONNECTION | |
|-----------------------|--------------------------|
| Connection: | 18i5 DALI 5m |
| Mounting: | Suspended, Wall, Ceiling |