



Ufo T High Bay





The Ufo T High Bay is ideal for commercial areas such as warehouses, workshops, and industrial halls. This LED fixture comes with a power switch, allowing you to easily set the desired output.

The Ufo T High Bay is both durable and energy-efficient. It has an IP65 rating for good protection against dust and water splashes. The fixture is available in various sizes and has a robust construction with an IK08 safety rating.



Lightsource Type:LED (built in)System Power [W]:240WCCT (Color Temperature):4000KCRI / Ra:80Lumen Output:43200lmLumen LED (tc=25):43200lmBeam Angle:105Lens (Diffuser):ClearDimming:DALIFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:18i5 DALI 5mMounting:Suspended, Wall, CeilingLiffetime [h]:L80B10: 100 000hLumen/W:26Olor:BlackLength [mm]:360mmHeight [mm]:360mmWidth [mm]:360mmDiameter [mm]:360mmWeight [kg]:2,4kgEmergency light testing:N/A	SPECIFICATIONS	
CCT (Color Temperature):4000KCRI / Ra:80Lumen Output:43200lmLumen LED (tc=25):43200lmBeam Angle:105Lens (Diffuser):ClearDimming:DALIFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:18i5 DALI 5mMounting:Suspended, Wall, CeilingLifetime [h]:L80B10: 100 000hLumen/W:26MacAdam (SDCM):3Color:BlackLength [mm]:169mmHeight [mm]:360mmWidth [mm]:360mmDiameter [mm]:360mmWeight [kg]:2,4kgEmergency Light [h]:No Emergency Light		LED (built in)
CRI / Ra:80Lumen Output:43200lmLumen LED (tc=25):43200lmBeam Angle:105Lens (Diffuser):ClearDimming:DALIFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:18i5 DALI 5mMounting:Lu80B10: 100 000hLifetime [h]:L80B10: 100 000hLumen/W:80lm/WUGR (<=):	System Power [W]:	240W
Lumen Output:43200lmLumen LED (tc=25):43200lmBeam Angle:105Lens (Diffuser):ClearDimming:DALIFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:18i5 DALI 5mMounting:Suspended, Wall, CeilingLifetime [h]:L80B10: 100 000hLumen/W:180lm/WUGR (<=):	CCT (Color Temperature):	4000K
Lumen LED (tc=25):43200lmBeam Angle:105Lens (Diffuser):ClearDimming:DALIFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:18i5 DALI 5mMounting:Suspended, Wall, CeilingLifetime [h]:180B10: 100 000hLumen/W:180Im/WUGR (<=):	CRI / Ra:	80
Beam Angle:105Lens (Diffuser):ClearDimming:DALIFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:18i5 DALI 5mMounting:Suspended, Wall, CeilingLifetime [h]:L80B10: 100 000hLumen/W:26MacAdam (SDCM):3Color:BlackLength [mm]:169mmHeight [mm]:360mmWidth [mm]:360mmDiameter [mm]:340mmWeight [kg]:2,4kgEmergency Light [h]:No Emergency Light	Lumen Output:	43200lm
Lens (Diffuser):ClearDimming:DALIFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:18i5 DALI 5mMounting:Suspended, Wall, CeilingLifetime [h]:L80B10: 100 000hLumen/W:180Im/WUGR (<=):	Lumen LED (tc=25):	43200lm
Dimming: DALI Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: 1815 DALI 5m Mounting: Suspended, Wall, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 180Im/W UGR (<=):	Beam Angle:	105
Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: 18i5 DALI 5m Mounting: Suspended, Wall, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 180Im/W UGR (<=):	Lens (Diffuser):	Clear
System Voltage [V]: 230V 50Hz Connection: 18i5 DALI 5m Mounting: Suspended, Wall, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 180Im/W UGR (<=):	Dimming:	DALI
Connection: 18i5 DALI 5m Mounting: Suspended, Wall, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 180lm/W UGR (<=):	Flickerfree:	Yes
Mounting: Suspended, Wall, Ceiling Lifetime [h]: L80B10: 100 000h Lumen/W: 180lm/W UGR (<=):	System Voltage [V]:	230V 50Hz
Lifetime [h]: L80B10: 100 000h Lumen/W: 180lm/W UGR (<=):	Connection:	18i5 DALI 5m
Lumen/W: 180lm/W UGR (<=):	Mounting:	Suspended, Wall, Ceiling
UGR (<=):	Lifetime [h]:	L80B10: 100 000h
MacAdam (SDCM): 3 Color: Black Length [mm]: 360mm Height [mm]: 169mm Width [mm]: 360mm Diameter [mm]: 360mm Weight [kg]: 2,4kg Emergency light [h]: No Emergency light	Lumen/W:	180lm/W
Color:BlackLength [mm]:360mmHeight [mm]:169mmWidth [mm]:360mmDiameter [mm]:360mmWeight [kg]:2,4kgEmergency light [h]:No Emergency light	UGR (<=):	26
Length [mm]: 360mm Height [mm]: 169mm Width [mm]: 360mm Diameter [mm]: 360mm Weight [kg]: 2,4kg Emergency light [h]: No Emergency light	MacAdam (SDCM):	3
Height [mm]: 169mm Width [mm]: 360mm Diameter [mm]: 360mm Weight [kg]: 2,4kg Emergency light [h]: No Emergency light	Color:	Black
Width [mm]:360mmDiameter [mm]:360mmWeight [kg]:2,4kgEmergency light [h]:No Emergency light	Length [mm]:	360mm
Diameter [mm]:360mmWeight [kg]:2,4kgEmergency light [h]:No Emergency light	Height [mm]:	169mm
Weight [kg]: 2,4kg Emergency light [h]: No Emergency light	Width [mm]:	360mm
Emergency light [h]: No Emergency light	Diameter [mm]:	360mm
	Weight [kg]:	2,4kg
Emergency light testing: N/A	Emergency light [h]:	No Emergency light
	Emergency light testing:	N/A