



## PRODUCT SHEET

Montana S

Art. no: 103020-30-GS-1

# NORLUX®

Lighting Solutions

## Montana S



Montana feature an innovative, tool-free system that allows for easy replacement of the electrical compartment directly on-site. This ensures fast and efficient maintenance while significantly reducing labor costs and downtime. The sleek and aerodynamic design minimizes wind resistance, enhances reliability, and optimizes heat dissipation, resulting in an extended lifespan. Built to withstand challenging conditions such as Nordic roads and high-altitude environments, Montana deliver dependable performance even in extreme settings.



### SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	30W
CCT (Color Temperature):	3000K
CRI / Ra:	70
Lumen Output:	4200lm
Lumen LED (tc=25):	4620lm
Beam Angle:	156°*54°
Lens (Diffuser):	PMMA
Dimming:	None
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	Cable 6m
Mounting:	Mast Ø60-76
Cut-out [mm]:	n/amm
Lifetime [h]:	L80B10: 100 000h
Lumen/W:	140lm/W
MacAdam (SDCM):	5
Color:	Grey
Length [mm]:	574mm
Height [mm]:	124mm
Width [mm]:	219mm
Diameter [mm]:	76mm
Weight [kg]:	4,9kg
Emergency light [h]:	No Emergency light
Emergency light testing:	N/A