NORLUX[®] Lighting Solutions

ART. NO. 103270-60-2 103270-60-3 103271-60-2 103271-60-3 103272-60-2 103272-60-3



NDL-A Downlight

▲ Safety Notes:

- The product must be installed, maintained, and operated as instructions below.
- Before starting installation of this product, make sure power supply is disconnected.
- Only to be installed by authorized electrician.
- Do not use abrasives or solvents when cleaning.
- Do not install the product if it appears damaged in any way. Check with manufacturer if in doubt.
- Do not modify this fitting in any matter as this will void warranty.
- Check protection class, if class I, it must be earthed.
- Disconnect power supply before maintenance or cleaning.

▲ Sikkerhetsinformasjon:

• Følg installasjonsmanual for korrekt montering.

(€≚

- Koble alltid fra strømmen før montering eller vedlikehold.
- Kan kun monteres av autorisert elektriker.
- Monter ikke produktet hvis det er synlig skade. Kontakt forhandler eller produsent.
- Bruk ikke løsemidler ved rengjøring
- Produktet skal ikke under noen omstendigheter endres eller modifiseres.
- Sjekk produktets isolasjonsklasse. Ved isolasjonsklasse I skal produktet jordes.

P Safety Instructions

before using the product: To ensure correct function and safety, please read and follow all instructions carefully

1. Turn off power supply before installation or before doing any maintenance work.

2. Do not install any luminaire near the heat source.

4. All wiring and installation of the light fitting must adhere to local and national wiring 3. Do not exceed the nominal supply voltage or amperage ratings.

5. Take care not to pull any electrical wires during unpacking as this may damage the rules.

Lay out all the components on a smooth surface and make sure there are no components connection. missing before assembling.

7. To avoid injury or damage to the fitting, please ensure that power leads and screws are

secure before connecting the power.

9. Please refer to IP(Ingress Protection) rating of this luminaire when deciding the location 8. Please keep instructions for future reference. of installation.

P Installation Instruction

Fig 1: Installation Spacing



Ceiling cutout table

Ceiling Cutout (mm)	Downlight diameter (mm)
Ø160-175	190 mm
Ø195-210	235 mm

IP rating table: Before installation, please check the IP label on the luminaire to choose the right place to install

IP44/IP54	IP20/IP40
Suitable for indoor areas including bathrooms and covered/sheltered areas such as porches.	Indoor use only, do not use in wet or damp place.

P65 Suitable for outdoor areas, not suitable for water immersion.

If the external flexible cable or cord of this lumnaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard. select preferred colour temperature for product in CCT change function only Cutout (refer to cutout table)



Dimmer selection table: Before installation, please check the information of driver as below.

DALI	0/1-10V	Triac dim	Non-dim
Only work with DALI dimming system, dimming range 8-100%.	Only work with 0/1-10V dimming system, dimming range 8-100%.	Compliable with recommended TRIAC dimmers, dimming range 8-100%.	Can not be used with any dimmer.

Installation Procedure

WARNING /

2.Switch on only after complete installation and examination of the circuit. 1.Switch off before installation.

3. Professional electrician for installation and maintenance only.



Downlight with external driver