



PRODUCT SHEET

Driver Phasecut 350mA max 18W 26-52V 18i3&EPN0034

Art. no: 0300-27



Driver Phasecut 350mA max 18W 26-52V 18i3&EPN003



SPECIFICATIONS

System Power [W]:	18W
Dimming:	Phase-Cut
CC or CV:	CC
CC [mA]:	350 - mA
CC (forward voltage driver) [V]:	26 - 52V
Max output voltage [V]:	62
Output Current Tolerance [%]:	5%
Current Ripple [%]:	15%
Current setting:	None
Expected Lifetime:	50000h
System Voltage [V]:	230V 50Hz V
Protection Class:	2
Dimming Minimum Level :	1%
Dimming Phasecut Type:	Leading / Trailing edge
Dimming output type:	Amplitude Modulation
Max load pr circuit - B10:	35
Max load pr circuit - B16:	56
Max load pr circuit - C10:	74
Max load pr circuit - C16:	118
Leakage current [mA]:	5mA
Inrush current I _{max} [A]:	5A
Inrush current time [μs]:	300μs
Manufacture:	AcTEC
Manufacture P/N:	D35018NTF - Driver 350mA cc 18W (26-52V)
Primary Connection:	18i3 male
Secondary Connection:	EPN0034 female
Length:	120mm



PRODUCT SHEET

Driver Phasecut 350mA max 18W 26-52V 18i3&EPN0034

Art. no: 0300-27



Height:	28mm
Width:	45mm
Weight:	0,15kg
Operating Temperature [°C]:	-20 - 50