



## PRODUCT SHEET

Driver on/off 600mA 25-13W 18i3 male/EPN0034

Art. no: 0300-44



# Driver on/off 600mA 25-13W 18i3 male/EPN0034



### SPECIFICATIONS

System Power [W]:	25-13W
Dimming:	None
Standby power P <sub>sb</sub> (W) <:	0,5
Flicker metric (P <sub>st</sub> LM) <:	1
Stroboscopic effect metric (SVM) <:	0,4
CC or CV:	CC
CV (driver) [V]:	33V
CC [mA]:	300 - 620mA
CC (forward voltage driver) [V]:	30 - 40V
Max output voltage [V]:	40
Output Current Tolerance [%]:	5%
Current Ripple [%]:	5%
Expected Lifetime:	50000h
System Voltage [V]:	230V 50Hz V
Protection Class:	2
Max load pr circuit - B10:	48
Max load pr circuit - B16:	76
Max load pr circuit - C10:	48
Max load pr circuit - C16:	76
Leakage current [mA]:	0,5mA
Inrush current I <sub>max</sub> [A]:	22,2A
Inrush current time [μs]:	53μs
Manufacture:	Up-Shine
Primary Connection:	18i3 male
Secondary Connection:	EPN0034 female
Color:	White