




Mika29 Pole





SPECIFICATIONS Lightsource Type: LED (replaceable) System Power [W]: 15W CCT (Color Temperature): 3000K CRI / Ra: 80 Lumen Output: 1875lm Lumen LED (tc=25): 1900lm Beam Angle: 140 Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 6m Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm Height [mm]: 523mm	CDECIFICATIONS	
System Power [W]: 15W CCT (Color Temperature): 3000K CRI / Ra: 80 Lumen Output: 1875lm Lumen LED (tc=25): 1900lm Beam Angle: 140 Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 6m Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm	SPECIFICATIONS	150/ 1 11)
CCT (Color Temperature): 3000K CRI / Ra: 80 Lumen Output: 1875lm Lumen LED (tc=25): 1900lm Beam Angle: 140 Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 6m Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm	•	LED (replaceable)
CRI / Ra: 80 Lumen Output: 1875lm Lumen LED (tc=25): 1900lm Beam Angle: 140 Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 6m Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm	System Power [W]:	15W
Lumen Output: 1875lm Lumen LED (tc=25): 1900lm Beam Angle: 140 Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 6m Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm	CCT (Color Temperature):	3000K
Lumen LED (tc=25): 1900lm Beam Angle: 140 Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 6m Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm	CRI / Ra:	80
Beam Angle: 140 Lens (Diffuser): Clear Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 6m Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm	Lumen Output:	1875lm
Lens (Diffuser):ClearDimming:NoneFlickerfree:YesSystem Voltage [V]:230V 50HzConnection:Cable 6mLifetime [h]:L80B10: 100 000hMacAdam (SDCM):4Color:AntraciteLength [mm]:500mm	Lumen LED (tc=25):	1900lm
Dimming: None Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 6m Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm	Beam Angle:	140
Flickerfree: Yes System Voltage [V]: 230V 50Hz Connection: Cable 6m Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm	Lens (Diffuser):	Clear
System Voltage [V]: 230V 50Hz Connection: Cable 6m Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm	Dimming:	None
Connection: Cable 6m Lifetime [h]: L80B10: 100 000h MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm	Flickerfree:	Yes
Lifetime [h]: MacAdam (SDCM): Color: Length [mm]: L80B10: 100 000h 4 Antracite 500mm	System Voltage [V]:	230V 50Hz
MacAdam (SDCM): 4 Color: Antracite Length [mm]: 500mm	Connection:	Cable 6m
Color: Antracite Length [mm]: 500mm	Lifetime [h]:	L80B10: 100 000h
Length [mm]: 500mm	MacAdam (SDCM):	4
-	Color:	Antracite
Height [mm]: 523mm	Length [mm]:	500mm
	Height [mm]:	523mm
Width [mm]: 500mm	Width [mm]:	500mm
Diameter [mm]: 500mm	Diameter [mm]:	500mm
Weight [kg]: 8,4kg	Weight [kg]:	8,4kg



The Mika29 Pole is ideal for illuminating outdoor areas such as gardens, driveways, and parking lots. It creates an inviting atmosphere while providing excellent visibility and enhanced safety. With an anthracite grey color (RAL7016) and an IP65 protection rating, it is well-protected against dust and water. Additionally, the product has an IK08 impact resistance, making it extra durable and perfect for outdoor use.