



PRODUCT SHEET

Driver DALI 700mA max 36W 30-42V 18i5 DALI/EPN0034

Art. no: 0300-2-17



Driver DALI 700mA max 36W 30-42V 18i5 DALI/EPN003



SPECIFICATIONS

System Power [W]:	36W
Dimming:	DALI2
Standby power Psb (W) <:	0,5
Flicker metric (Pst LM) <:	0,4
Stroboscopic effect metric (SVM) <:	0,1
CC or CV:	CC
CC [mA]:	700 - 850mA
CC (forward voltage driver) [V]:	30 - 42V
Max output voltage [V]:	60
Output Current Tolerance [%]:	5%
Current Ripple [%]:	4%
Current setting:	DIP-switch
Expected Lifetime:	50000h
System Voltage [V]:	230V 50Hz V
Protection Class:	2
Dimming Minimum Level :	1%
Dimming output type:	Amplitude Modulation
Max load pr circuit - B10:	28
Max load pr circuit - B16:	36
Max load pr circuit - C10:	37
Max load pr circuit - C16:	50
Leakage current [mA]:	0,7mA
Inrush current Imax [A]:	16,5A
Inrush current time [μs]:	177μs
Manufacture:	Philips
Primary Connection:	18i5 DALI male
Secondary Connection:	EPN0034 female



PRODUCT SHEET

Driver DALI 700mA max 36W 30-42V 18i5 DALI/EPN0034

Art. no: 0300-2-17



Color:

White