




FDV SPEC SHEET

Riva G2

Art. no: 102601-00-1



Riva G2



Art. no: 102601-00-1



FDV SPEC SHEET

Riva G2

Art. no: 102601-00-1

NORLUX®

Lighting Solutions

LIGHT TECHNICAL

Lightsources Type:	LED (built in)
Lumen Output:	650
Lumen LED (tc=25):	65
Beam Angle:	120°
CCT (Color Temperature):	3000
CRI / Ra:	90
Color Code:	930
MacAdam (SDCM):	3
Lens (Diffuser):	Frosted
UGR (<=):	26
Dimming:	None
Flickerfree:	Yes
System Power [W]:	7.2
System Voltage [V]:	24VDC
Protection Class:	2
Socket / Cap-Base:	N/A
Current Output [mA]:	150
Voltage Forward Min [V]:	3
Voltage Forward Max [V]:	3,4
Connection:	Riva 2-pin Connector
Mounting:	Surface, Wall, Ceiling
Ingress Protection:	IP44
Impact Protection:	IK08
Operating Temperature [°C]:	-20 - 40
Lifetime [h]:	L80B10: 100 000
Color:	Silver
Length [mm]:	525
Height [mm]:	14
Width [mm]:	20
Weight [kg]:	0,116
Housing Material :	Aluminium 6063
Diffuser Material:	Polycarbonate
Material 2:	PCB board: Silica, vitreous Al