




## FDV SPEC SHEET

NSW M Pro Dual 2300lm 2700K-6500K RGBWW 30W 24° Recessed BK

Art. no: 103240-24-2



# NSW M Pro Dual 2300lm 2700K-6500K RGBWW 30W 24



Art. no: 103240-24-2

### LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	2300
Lumen LED (tc=25):	2500
Beam Angle:	24°
CCT (Color Temperature):	2700-6500K
CRI / Ra:	90
Color Code:	RGBW
MacAdam (SDCM):	3
Lens (Diffuser):	Lens

### MOUNTING / CONNECTION

Connection:	QuickConnect
Cut-out [mm]:	110
Mounting:	Recessed

### ELECTRICAL DATA

UGR (<=):	7
Dimming:	AIOT or APP (Bluetooth connected)
Flickerfree:	Yes
System Power [W]:	30
System Voltage [V]:	230V 50Hz
Protection Class:	2
Current Output [mA]:	720
Voltage Forward Min [V]:	36
Voltage Forward Max [V]:	36



## FDV SPEC SHEET

NSW M Pro Dual 2300lm 2700K-6500K RGBWW 30W 24° Recessed BK  
Art. no: 103240-24-2



PRODUCT	
To be recessed in insulation:	No
Ingress Protection:	IP20
Impact Protection:	IK06
Operating Temperature [°C]:	-10 - 30
Lifetime [h]:	L80B10: 100 000
Color:	Black
RAL:	RAL7021
Height [mm]:	175
Width [mm]:	118
Diameter [mm]:	118
Weight [kg]:	1,125