



PRODUCT SHEET

Z line

Art. no: 102083-2-00-1-ddd

NORLUX®

Lighting Solutions

Z line



Z Line is an LED fixture designed with a focus on energy savings and efficient installation. It utilizes the latest LED technology, providing up to 180 lm/W. The fixture features a 2,5mm² throughwiring and quick connections on both ends, making installation simple and fast without the need to open the fixture. The fixture is made of galvanized steel and is available in two lengths; 1420mm with 42W in 3000K and 4000K, 1700mm with 42W and 72W in 3000K and 4000K. All versions can be ordered with DALI2.



SPECIFICATIONS

Lightsource Type:	LED (built in)
System Power [W]:	74W
CCT (Color Temperature):	3000K
CRI / Ra:	80
Lumen Output:	13040lm
Lumen LED (tc=25):	13500lm
Beam Angle:	70°
Lens (Diffuser):	Lens
Dimming:	DALI2
Flickerfree:	Yes
System Voltage [V]:	230V 50Hz
Connection:	QuickConnect
Mounting:	Surface, Ceiling
Lifetime [h]:	L80B10: 100 000h
Lumen/W:	176lm/W
MacAdam (SDCM):	3
Through-wiring (mm ²):	5x2,5
Color:	Steel
Length [mm]:	1700mm
Height [mm]:	69mm
Width [mm]:	86mm
Weight [kg]:	4kg