



## FDV SPEC SHEET

Ufo Y 36000lm 840 120° 200W BK 5m 18i5 DALI

Art. no: 102655-02-2-ddd



# Ufo Y 36000lm 840 120° 200W BK 5m 18i5 DALI



Art. no: 102655-02-2-ddd

### LIGHT TECHNICAL

|                          |                |
|--------------------------|----------------|
| Lightsource Type:        | LED (built in) |
| Lumen LED (tc=25):       | 36000          |
| Beam Angle:              | 120°           |
| CCT (Color Temperature): | 4000           |
| CRI / Ra:                | 80             |
| Color Code:              | 840            |
| Lens (Diffuser):         | Clear          |

### PRODUCT

|                     |                 |
|---------------------|-----------------|
| Ingress Protection: | IP65            |
| Impact Protection:  | IK08            |
| Lifetime [h]:       | L80B10: 100 000 |
| Color:              | Black           |
| Height [mm]:        | 122             |
| Diameter [mm]:      | 330             |

### ELECTRICAL DATA

|                                      |           |
|--------------------------------------|-----------|
| Dimming:                             | DALI      |
| System Power [W]:                    | 200       |
| System Voltage [V]:                  | 230V 50Hz |
| Protection Class:                    | 1         |
| Max load pr circuit - B10:           | 9         |
| Max load pr circuit - B16:           | 14        |
| Max load pr circuit - C10:           | 12        |
| Max load pr circuit - C16:           | 18        |
| Inrush current I <sub>max</sub> [A]: | 63        |
| Inrush current time [μs]:            | 144       |

### MOUNTING / CONNECTION

|             |              |
|-------------|--------------|
| Connection: | 18i5 DALI 5m |
|-------------|--------------|