



FDV SPEC SHEET

NDL240-B

Art. no: 102793-2-60-2



NDL240-B



Art. no: 102793-2-60-2

LIGHT TECHNICAL

| | |
|--------------------------|----------------|
| Lightsource Type: | LED (built in) |
| Lumen Output: | 2600 |
| Lumen LED (tc=25): | 2800 |
| Beam Angle: | 60° |
| CCT (Color Temperature): | 3000 |
| CRI / Ra: | 90 |
| Color Code: | 930 |
| MacAdam (SDCM): | 3 |
| Lens (Diffuser): | Clear |

MOUNTING / CONNECTION

| | |
|---------------|-------------------|
| Connection: | EPN0024 |
| Cut-out [mm]: | 195-230 |
| Mounting: | Recessed, Ceiling |

ELECTRICAL DATA

| | |
|--------------------------|---------------------|
| UGR (<=): | 19 |
| Dimming: | Depending on Driver |
| Flickerfree: | Yes |
| System Power [W]: | 25 |
| System Voltage [V]: | 230V 50Hz |
| Protection Class: | 2 |
| Socket / Cap-Base: | N/A |
| Current Output [mA]: | 650 |
| Voltage Forward Min [V]: | 30 |
| Voltage Forward Max [V]: | 40 |
| Emergency light [h]: | No Emergency light |
| Emergency light testing: | N/A |



FDV SPEC SHEET

NDL240-B

Art. no: 102793-2-60-2



| PRODUCT | |
|-------------------------------|-----------------|
| To be recessed in insulation: | Not applicable |
| Ingress Protection: | IP44 |
| Impact Protection: | IK06 |
| Operating Temperature [°C]: | -20 - 45 |
| Lifetime [h]: | L80B10: 100 000 |
| Color: | Black |
| RAL: | RAL9005 |
| Length [mm]: | 240 |
| Height [mm]: | 142 |
| Width [mm]: | 240 |
| Diameter [mm]: | 240 |
| Weight [kg]: | 0,93 |
| Housing Material : | Aluminium |
| Diffuser Material: | Aluminium 6063 |