



FDV SPEC SHEET

Luno Track 3500lm 930/935/940 90° 28W BK 3-cir
Art. no: 103410-90-2



Luno Track 3500lm 930/935/940 90° 28W BK 3-cir



Art. no: 103410-90-2

LIGHT TECHNICAL

Lightsource Type:	LED (built in)
Lumen Output:	3300
Lumen LED (tc=25):	3500
Beam Angle:	90°
CCT (Color Temperature):	30/35/4000K
CRI / Ra:	90
Color Code:	930/935/940
MacAdam (SDCM):	3
Lens (Diffuser):	Micropris.
UGR (<=):	23

MOUNTING / CONNECTION

Connection:	Track 3-Circuit
Mounting:	Track, Ceiling

ELECTRICAL DATA

Dimming:	None
Flickerfree:	Yes
Flicker metric (Pst LM) <:	0,07
Stroboscopic effect metric (SVM) <	0,07
System Power [W]:	28
System Voltage [V]:	230V 50Hz
Protection Class:	2
Max load pr circuit - B10:	15
Max load pr circuit - B16:	23
Max load pr circuit - C10:	36
Max load pr circuit - C16:	37
Inrush current I _{max} [A]:	14,2
Inrush current time [μs]:	227
Socket / Cap-Base:	N/A
Current Output [mA]:	65
Voltage Forward Max [V]:	2,82
Emergency light [h]:	No Emergency light
Emergency light testing:	N/A



FDV SPEC SHEET

Luno Track 3500lm 930/935/940 90° 28W BK 3-cir
Art. no: 103410-90-2



PRODUCT	
Ingress Protection:	IP20
Impact Protection:	IK06
Operating Temperature [°C]:	25 -
Lifetime [h]:	L80B10: 100 000
Color:	Black
Height [mm]:	212,9
Diameter [mm]:	300
Weight [kg]:	1,26