




FDV SPEC SHEET
Leila C Midi Surface
Art. no: 101365-70-2-ddd



Leila C Midi Surface



Art. no: 101365-70-2-ddd

LIGHT TECHNICAL

Lumen Output:	3366
Lumen LED (tc=25):	4750
Beam Angle:	70°
CCT (Color Temperature):	3000
CRI / Ra:	80
Color Code:	830
MacAdam (SDCM):	3
Lens (Diffuser):	Clear

MOUNTING / CONNECTION

Connection:	QuickConnect
Mounting:	Ceiling, Surface

ELECTRICAL DATA

Dimming:	DALI
Dimming Output Type:	Amplitude Modulation
System Power [W]:	31
System Voltage [V]:	230V 50Hz
Protection Class:	1
Max load pr circuit - B10:	35
Max load pr circuit - B16:	55
Max load pr circuit - C10:	56
Max load pr circuit - C16:	94
Inrush current I _{max} [A]:	20
Inrush current time [μs]:	50
Socket / Cap-Base:	N/A
Current Output [mA]:	800



FDV SPEC SHEET

Leila C Midi Surface

Art. no: 101365-70-2-ddd



PRODUCT

To be recessed in insulation:	No
Ingress Protection:	IP20
Impact Protection:	IK00
Operating Temperature [°C]:	-25 - 50
Lifetime [h]:	L80B10: 100 000
Color:	Black
Height [mm]:	150
Width [mm]:	190
Weight [kg]:	1,5